

PAT-NO: JP404098795A

DOCUMENT-IDENTIFIER: JP 04098795 A

TITLE: DISCHARGE LAMP LIGHTING DEVICE

PUBN-DATE: March 31, 1992

INVENTOR-INFORMATION:

NAME

ONISHI, MASAHIRO

KANDA, TAKASHI

ASSIGNEE-INFORMATION:

NAME

COUNTRY

MATSUSHITA ELECTRIC WORKS LTD

N/A

APPL-NO: JP02215161

APPL-DATE: August 14, 1990

INT-CL (IPC): H05B041/24

ABSTRACT:

PURPOSE: To supply energy from a power source of voltage for lighting a lamp, directly to a filament, so as to further reduce the size of a discharge lighting device by providing a switch device for switching to a power source, a switching device, and to the filament, which are formed in a loop, at the time of pre- heating the filament of the lamp.

CONSTITUTION: When a switch device SW<SB>2</SB> is turned OFF, the current If supplied to filaments f<SB>1</SB>, f<SB>2</SB>, are cut, and a switching operation is actuated through a lamp L, and currents IL, IS that have slants

BEST AVAILABLE COPY

GH
(2 of 2)

according to the property of the lamp, are let run. In a method of supplying current to the lamp L through the switching of a switching device SW<SB>1</SB>, by providing the switch SW<SB>2</SB>, the pre-heating by pulsed current is achieved, utilizing the property of each filament f<SB>1</SB>, f<SB>2</SB> of the lamp L, omitting the need to provide another power source for preheating, and the size of a device can thus be reduced. Regarding the operation of the switching device, the same pattern is obtained even when the ON condition of the SW<SB>1</SB> is maintained during pre-heating, while ON/OFF operation is carried out by the SW<SB>2</SB>.

COPYRIGHT: (C)1992,JPO&Japio